



COVERS FOR RV INDUSTRY

CUSTOM FIT PROTECTION FOR RECREATIONAL VEHICLES

Since 1994, Transshield covers have provided protection from the elements during transportation and storage. Weather and road conditions can wreak havoc on poorly covered RV's. Transshield covers provide protection from road debris, UV rays, corrosion, moisture, mildew, and general surface damage thereby reducing exposure to warranty and repair issues.



ADVANCED PROTECTIVE COVER TECHNOLOGY

Transshield covers are made from Shrinkable Fabric™ and consist of three layers: an outer layer, that resists UV-rays and prevents condensation, a middle adhesive layer and a soft inner layer. These heat shrink covers feature the patented Vapor Corrosion Inhibitor (VCI) system which provides maximum protection from corrosion during transportation and storage.



WHY TRANSHIELD WORKS



WATERPROOF FABRICS — Moisture, rain, snow, and sleet will not penetrate the cover. Transshield products have proven effective in all climates.



LIGHTWEIGHT — Depending on the material, the weight is between 0.20 - 1.25 lbs per square yard. Most covers can be installed by one-two people.

RH%

ANTI-CONDENSATING — Moisture under the cover is pulled toward the outside of the cover via the capillary and moisture surface tension properties of the technology. Moisture is removed and relative humidity is reduced.



CUSTOM FIT — Our design process ensures a custom-fit cover that is reinforced at all wear points. Access points are developed in accordance with customer desires.



VAPOR CORROSION INHIBITOR (available) — Reduces corrosion by as much as 95%. Effective on multiple metals. Majority of VCI is emitted inward toward the protected equipment. VCIs do not contain nitrites, nitrates, or hazardous materials.



PROTECTION FROM DEGRADATION — Protects from harmful UV rays, rain, snow, sleet, dust, sand, wind, and airborne pollutants (ash, etc.).



REUSABLE — Transshield XT and ArmorDillo® can be installed and removed on a daily basis. Storage bags are available for protection of cover or transport on vehicles when not in use.



SOFT INSIDE — Aids in ease of installation and protects Class A surfaces and expensive CARC paint surfaces.



PATENTED — Awarded 9 international patents.



DURABLE — Service life of several years, even in the harshest environments.

SPECS

FABRICS	FL	5 MIL	7 MIL	10 MIL	XT	ARMORDILLO
COLORS	black	white	white, tan, blue, green, red	white	tan, green	tan, green, gray, red, blue, black
TOTAL THICKNESS	25 MIL	20 MIL	23 MIL	32 MIL	45 MIL	60 MIL
WEIGHT (lbs/yd ^2)	0.5	0.3	0.4	0.6	0.7	1.25
LINING	nonwoven	nonwoven	nonwoven	nonwoven	scrim reinforced nonwoven**	scrim reinforced nonwoven**
STRENGTH Load bearing (lbs) MD/CD average	189	46	35	45	120	288
EXPECTED LIFE (years)	n/a	2	2	2	2-4	2-4
SHRINKABLE/ NON-SHRINKABLE	non-shrinkable	shrinkable	shrinkable	shrinkable	non-shrinkable	non-shrinkable
WATER VAPOR TRANSMISSION (g/m^2/day)	n/a	3.1*	3.1	2*	5	1000

*Estimated Value

**Proprietary Transshield Product

Numbers subject to change without notice

888.731.7700

GENERAL@TRANSHIELD-USA.COM

TRANSHIELD-USA.COM



Copyright © 2022 Transshield. All rights reserved.