



COVERS FOR MARINE INDUSTRY

PROTECT FROM THE ELEMENTS

Nature – wild and untamed – assails boats and other watercraft daily, with everything it's got. Sun, wind, rain, and snow from the outside; moisture, mold and mildew on the inside. And that's just during storage. When transporting, road debris, dirt and grime will assail it for miles on end.

But keeping nature's forces at bay isn't as simple

as wrapping plastic around your boat. You need to protect against every element, something everyday solutions simply can't do.

To take control and protect against the forces of nature and the open road, there's Transshield. Our advanced cover technology guards against whatever nature has to bring.

A BETTER WAY TO PROTECT

Since Transshield covers are custom designed to fit your particular boat model, they are easy to install. A team of two can cover and shrink a midsize (up to 21') boat in less than five (5) minutes. And because they are made to withstand harsh elements and endure long transportation journeys, they save you installation time and warranty claim dollars in the end. Take control and protect your boat against the forces of nature.



WHY TRANSHIELD WORKS



WATERPROOF FABRICS – Moisture, rain, snow, and sleet will not penetrate the cover. Transshield products have proven effective in all climates.

RH%

ANTI-CONDENSATING – Moisture under the cover is pulled toward the outside of the cover via the capillary and moisture surface tension properties of the technology. Moisture is removed and relative humidity is reduced.



VAPOR CORROSION INHIBITOR (available) – Reduces corrosion by as much as 95%. Effective on multiple metals. Majority of VCI is emitted inward toward the protected equipment. VCIs do not contain nitrites, nitrates, or hazardous materials.



DURABLE – Service life of several years, even in the harshest environments.



SOFT INSIDE – Aids in ease of installation and protects Class A surfaces and expensive CARC paint surfaces.



LIGHTWEIGHT – Depending on the material, the weight is between 0.20 - 1.25 lbs per square yard. Most covers can be installed by one-two people.



CUSTOM FIT – Our design process ensures a custom-fit cover that is reinforced at all wear points. Access points are developed in accordance with customer desires.



PROTECTION FROM DEGRADATION – Protects from harmful UV rays, rain, snow, sleet, dust, sand, wind, and airborne pollutants (ash, etc.).

SPECS

FABRICS	5 MIL	7 MIL	10 MIL
COLORS	white	white, tan, blue, green, red	white
TOTAL THICKNESS	20 MIL	23 MIL	32 MIL
WEIGHT (lbs/yd ^2)	0.3	0.4	0.6
LINING	nonwoven	nonwoven	nonwoven
STRENGTH Load bearing (lbs) MD/CD average	46	35	45
EXPECTED LIFE (years)	2	2	2
SHRINKABLE/ NON-SHRINKABLE	shrinkable	shrinkable	shrinkable
WATER VAPOR TRANSMISSION (g/m^2/day)	3.1*	3.1	2*

*Estimated Value
Numbers subject to change without notice
For information on our patented technologies and products, visit www.transshield-usa.com/resources/patents/

WHY VCI?

Covers containing VCI have proven to be effective in fighting the formation of corrosion.

